




www.franceraccord.fr
BY HARDOUIN

FICHE TECHNIQUE

RACCORD PVC PRESSION

EMBOUT TARAUDÉ

3 Diamètres - mâle / femelle à coller x femelle à visser



Référence	d1	d	G	l	Z	S	Gr
ET20161/4	20	16	1/4"	37	-	32	19
ET20163/8	20	16	3/8"	39	-	32	19
ET20161/2	20	16	1/2"	43	-	32	21
ET20163/4	20	16	3/4"	44	-	32	27
ET25161/2	25	16	1/2"	41	12	32	25
ET25201/2	25	20	1/2"	41	11	32	20
ET25203/4	25	20	3/4"	45	10	38	29
ET25201	25	20	1"	45	9	46	40
ET32251/2	32	25	1/2"	45	10	32	27
ET32253/4	32	25	3/4"	47	10	38	34
ET32251	32	25	1"	48	10	46	45
ET322511/4	32	25	1"1/4	50	10	53	56
ET40323/4	40	32	3/4"	51	10	41	40
ET40321	40	32	1"	52	9	46	48
ET403211/4	40	32	1"1/4	54	8	53	60
ET403211/2	40	32	1"1/2	59	13	65	97
ET504011/4	50	40	1"1/4	55	7	53	65
ET504011/2	50	40	1"1/2	64	14	65	108
ET50402	50	40	2"	66	11	78	133
ET635011/2	50	63	1"1/2	69	11	65	128
ET63502	50	63	2"	71	11	78	154
ET635021/2	50	63	2"1/2	80	11	92	206
ET75632	75	63	2"	76	11	78	170
ET756321/2	75	63	2"1/2	87	13	92	214
ET75633	75	63	3"	89	18	112	316
ET907521/2	90	75	2"1/2	95	20	92	260
ET90753	90	75	3"	97	20	112	360
ET90754	90	75	4"	124	-	135	620
ET110903	110	90	3"	107	22	112	480
ET110904	110	90	4"	116	-	135	733

*Ces fiches sont la propriété de Franceraccord. Des modifications peuvent être apportées sans préavis.
Les caractéristiques sont données à titre indicatif et les photos ne sont pas contractuelles.*