




www.franceraccord.fr
BY HARDOUIN

FICHE TECHNIQUE

RACCORD PVC PRESSION

REDUCTION

Mâle X Femelle à visser



Référence	G	G1	L	Z	S	PN	Gr
RMF3/81/4	3/8"	1/4"	26	14	19	10	6
RMF1/23/8	1/2"	3/8"	32	19	24	10	10
RMF3/43/8 ¹	3/4"	3/8"	36,4	25	30	10	16
RMF3/41/2	3/4"	1/2"	39	25	32	10	23
RMF13/8 ¹	1"	3/8"	39,4	28	36	10	25
RMF11/2	1"	1/2"	42	31	32	10	27
RMF13/4	1"	3/4"	45	29	38	10	35
RMF11/41/2	1"1/4	1/2"	46	32	32	10	41
RMF11/43/4	1"1/4	3/4"	50	34	38	10	49
RMF11/41	1"1/4	1"	50	32	46	10	59
RMF11/21/2	1"1/2	1/2"	48	32	32	10	45
RMF11/23/4	1"1/2	3/4"	51	34	38	10	52
RMF11/21	1"1/2	1"	52	32	46	10	60
RMF11/211/4	1"1/2	1"1/4	55	34	55	10	76
RMF23/4	2"	3/4"	55	37	38	10	78
RMF21	2"	1"	55	36	46	10	86
RMF211/4	2"	1"1/4	58	37	55	10	98
RMF211/2	2"	1"1/2	60	36	64	10	119
RMF21/211/4 ¹	2"1/2	1"1/4	64,4	43	80	10	135
RMF21/211/2 ¹	2"1/2	1"1/2	64,4	43	80	10	135
RMF21/22	2"1/2	2"	37	61	79	10	160
RMF311/2 ¹	3"	1"1/2	66	41	93	10	204
RMF32 ¹	3"	2"	72,7	47	95	10	210
RMF321/2 ¹	3"	2"1/2	77,2	47	95	10	198
RMF42 ¹	4"	2"	78,7	53	120	10	334
RMF421/2 ¹	4"	2"1/2	83,2	53	120	10	337
RMF43 ¹	4"	3"	86,3	53	120	10	351

*Ces fiches sont la propriété de Franceraccord. Des modifications peuvent être apportées sans préavis.
Les caractéristiques sont données à titre indicatif et les photos ne sont pas contractuelles.*